

CONTROLLER PED 2500



- Meets JSS 55555 military standard.
- Hard potted.
- Reverse polarity protected.
- Output shortcircuit protected.
- Ideal/Run facility.
- Compatible for synchronization.
- Variable droop.
- Compatible with different actuators.
- Field adjustable.
- No software used.
- 7G vibration proof.

Performance :

Isochronous Operation / Steady State Stability	±0.25% or better
Speed Range/Governor	1K – 10K Hz continuous
Speed Drift With Temperature	±1% maximum
Idle Adjust CW	Min. 1200 Hz. Below set speed
Idle Adjust CCW	Min. 4100 Hz. Below set speed
Droop Range	1 – 5% regulation*
Droop Adjust Max.H-G Jumper	875 Hz., ±75Hz.per 1.0A change
Droop Adjust Min. No jumper	31 Hz, ±6 Hz. Per 1.0A change
Speed Trim Range	±200 Hz
Maximum current	10 Amps @ 12V
	6 Amps @ 24V
Operatig voltage	10 to 30 V DC

PRECISION ELECTRODYNAMICS

NO. 1/5, UNION CHAMBERS, OPP. APPOLLO TYRES LIMITED, NORTH KALAMASSERY,
ALAWYE, KERALA - 683104 • PHONE / FAX : (0484) 2551758